

WAN
 Auto PVC
 ATM
 ADSL
 LAN
 WLAN

WAN Physical Type: ADSL WAN Ethernet WAN

Default Route Selection: Auto Specified 1

VPI: 2 VCI: 3

Encapsulation: LLC VC-Mux 4

Channel Mode: 5

Enable IGMP: 6

IP Protocol:

PPP Settings:

User Name: 7 Password: 8

Type: Idle Time (min):

WAN IP Settings:

Type: Fixed IP DHCP

IP Address: ISP Gateway:

اتصل بمزود الانترنت الخاص بك
 للحصول على اسم المستخدم
 وكلمة المرور

WAN IP Settings:

Type: Fixed IP DHCP

IP Address: ISP Gateway:

Subnet Mask:

Primary DNS Server: Secondary DNS Server:

Default Route: Disable Enable Auto

Unnumbered: 9

IPv6 WAN Setting:

Address Mode:

IPv6 DNS Mode:

DHCPv6 Mode:

Request DHCPv6 PD: 10

Connect Disconnect Add Modify Delete Undo Refresh

هنا يجب الضغط على زر **MODIFY**

في القناة يلي تم تأسيسها لخدمة **ip-TV**

وتفعيل الخيار المبين Bridged Ethernet (Transparent Bridging)

وبعدها الضغط على زر **OK**

PPP Interface - Modify

Protocol:	PPPoE
ATM VCC:	0/32
Login Name:	<input type="text"/>
Password:	<input type="text"/>
Authentication Method:	AUTO ▾
Connection Type:	Continuous ▾
Idle Time (s):	0
Bridge:	<input checked="" type="radio"/> Bridged Ethernet (Transparent Bridging) <input type="radio"/> Bridged PPPoE (implies Bridged Ethernet) <input type="radio"/> Disable Bridge
AC Name:	<input type="text"/>
Service Name:	<input type="text"/>

- WLAN
- LAN**
- LAN
- DHCP
- DHCP Static
- LAN IPv6
- WLAN

LAN Interface Setup

This page is used to configure the LAN interface of your ADSL Router. Here you may change the setting for IP address, subnet mask, etc.

Interface Name:	Ethernet1
IP Address:	<input type="text" value="192.168.1.1"/>
Subnet Mask:	<input type="text" value="255.255.255.0"/>
<input type="checkbox"/> Secondary IP	
IGMP Snooping:	<input type="radio"/> Disable <input checked="" type="radio"/> Enable

11

Apply Changes

LAN Port:	<input type="text"/>
Link Speed/Duplex Mode:	<input type="text"/>

Modify

ETHERNET Status Table:

Select	Port	Link Mode
<input type="checkbox"/>	LAN1	AUTO Negotiation

- Route**
- Static Route
- IPv6 Static Route
- RIP
- NAT
- QoS
- CWMP
- Port Mapping
- Others

Routing Configuration

This page is used to configure the routing information. Here you can add/delete IP routes.

Enable:	<input checked="" type="checkbox"/>
Destination:	<input type="text" value="10.237.239.0"/>
Subnet Mask:	<input type="text" value="255.255.255.0"/>
Next Hop:	<input type="text"/>
Metric:	<input type="text" value="1"/>
Interface:	<input type="text"/>

12

13

14

15

Add Route Update Delete Selected Show Routes

Static Route Table:

Select	State	Destination	Subnet Mask	NextHop	Metric	Itf
--------	-------	-------------	-------------	---------	--------	-----