

Interface	Quick Start	Interface Setup	Advanced Setup	Access Management	Maintenance	Status	Help
	Internet	LAN	Wireless				
QoS	VPI: 0 (range: 0~255) VCI: 32 (range: 1~65535)		تقوم بوضع القيم التالية VPI=0 VCI=32				
	ATM QoS: UBR PCR: 0 cells/second SCR: 0 cells/second MBS: 0 cells						
Encapsulation	ISP: <input type="radio"/> Dynamic IP Address <input type="radio"/> Static IP Address <input checked="" type="radio"/> PPPoA/PPPoE <input type="radio"/> Bridge Mode		نختار PPPoA/PPPoE				
PPPoE/PPPoA	اتصل بمزود الانترنت الخاص بك للحصول على اسم المستخدم وكلمة المرور		Servicename: _____ Username: _____ Password: _____		تقوم بوضع اسم المستخدم وكلمة المرور الافتراضيين لخدمة IPTV Username: ..... Password: .....		
	Encapsulation: PPPoE LLC Bridge Interface: <input checked="" type="radio"/> Activated <input type="radio"/> Deactivated		تقوم باختيار القيمة Activated للـ Bridge Interface				

Interface	Quick Start	Interface Setup	Advanced Setup	Access Management	Maintenance	Status	Help
	Internet	LAN	Wireless				
Connection Setting	Bridge Interface: <input checked="" type="radio"/> Activated <input type="radio"/> Deactivated						
	Connection: <input checked="" type="radio"/> Always On (Recommended) <input type="radio"/> Connect On-Demand (Close if idle for 0 minutes) <input type="radio"/> Connect Manually						
IP Address	TCP MSS Option: TCP MSS(default 1400) 1400 bytes						
	Get IP Address: <input type="radio"/> Static <input checked="" type="radio"/> Dynamic Static IP Address: 0.0.0.0 IP Subnet Mask: 0.0.0.0 Gateway: 0.0.0.0						
	NAT: Enable Default Route: <input type="radio"/> Yes <input checked="" type="radio"/> No		نضع القيمة No للخيار Default Route				
	TCP MTU Option: TCP MTU(default 1480) 1480 bytes Dynamic Route: RIP2-B Direction: Both Multicast: IGMP v2						
	IGMP v2 للخيار Multicast نضع القيمة IGMP v2 للخيار						

SAVE DELETE

Advanced | Quick Start | Interface Setup | **Advanced Setup** | Access Management | Maintenance | Status | Help

Firewall | Routing | NAT | QoS | VLAN | ADSL

**Routing Table List**

#	Dest IP	Mask	Gateway IP	Metric	Device	Use	Edit	Drop
1	10.10.10.5	32	10.10.10.5	1	poe4	0		
2	10.237.239.1	32	10.237.239.1	1	poe0	0		
3	192.168.1.0	24	192.168.1.1	1	eno10	5369248		
4	10.237.239.0	24	PVC0	1	poe0	15		
5	default	0	Node5	2	poe4	3769840		

**ADD ROUTE**

Advanced | Quick Start | Interface Setup | **Advanced Setup** | Access Management | Maintenance | Status | Help

Firewall | Routing | NAT | QoS | VLAN | ADSL

**Static Route**

Destination IP Address: 10.237.239.0  
 IP Subnet Mask: 255.255.255.0  
 Gateway IP Address:  0.0.0.0  PVC0  
 Metric: 1  
 Announced in RIP: Yes

SAVE DELETE BACK CANCEL

نقوم بوضع القيم كما في الصورة التالية